

Universal Thru-the-wall Air Conditioners

Uni-fit®

Universal fit for easy replacement

Chassis installs into many competitive sleeves with included accessories

Quiet and energy efficient



IDEAL for new construction, retrofits and residential remodeling.

COMPLETELY PROGRAMMABLE with automatic features and remote control for easy operation (cooling models).

- High efficiency operation saves on energy costs
- Rotary compressors provide quiet, dependable performance
- Cooling only and cooling with electric heat models available
- 4-way air flow control
- Stale air exhaust
- Permanent filter
- Seacoast protection

COOLING MODELS feature electronic controls with remote and 3 cooling/ 3 fan-only speeds

HEAT/COOL MODELS feature 2 cooling and 2 heating speeds, plus 1 fan-only setting



[Actual product appearance may vary]



IMPORTANT NOTE: Optional sleeves (MODEL USC) are sold and shipped separately to accommodate new construction and replacement requirements

Friedrich®

Uni-fit® Universal Thru-the-wall Air Conditioners

★ ENERGY STAR® qualified models

MODEL		US08B10A★	UE08A13B	US10B10A★	US10B30A★	UE10A33B	US12B10A★	US12B30A★	UE12A33B
Performance									
BTU/h	(Cooling)	8000	8000	10000	10000/9800	10000/9800	11700	11700/11400	11700/11400
	(Electric Heating)	None	3850	None	None	11200/9200	None	None	11200/9200
EER		9.6	9.6	9.4	9.4/9.4	9.4/9.4	9.4	9.4/9.4	9.4/9.4
COP		None	None	None	None	None	None	None	None
Dehumidification	(Pts/Hr)	2.2	2.2	3.2	3.2	3.2	3.9	3.8	3.8
Dry Air Flow	(CFM) H / L	260/220	260/220	285/225	285/225	285/225	290/230	290/230	290/230
dBA Level	(Indoor / Outdoor)	49/59	49/59	51/60	51/60	51/60	52/61	52/61	52/61
Electrical Ratings									
Voltage / 60 Hz		115	115	115	230/208	230/208	115	230/208	230/208
Watts	(Cooling)	830	830	1060	1060/1040	1060/1040	1250	1250/1210	1250/1210
	(Electric Heating)	None	1230	None	None	3500/2900	None	None	3500/2900
Rated Amps	(Cooling)	7.5	7.5	9.8	4.7/5.2	4.7/5.2	11.6	5.8/6.2	5.8/6.2
	(Electric Heating)	None	10.7	None	None	15.3/14.0	None	None	15.3/14.0
Features									
Control Type		ELECTRONIC	MECHANICAL	ELECTRONIC	ELECTRONIC	MECHANICAL	ELECTRONIC	ELECTRONIC	MECHANICAL
Remote Control		Yes	—	Yes	Yes	—	Yes	Yes	—
Open Inlet Grille (for retrofit situations)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Thermostat Control		Thermistor	Thermostat	Thermistor	Thermistor	Thermostat	Thermistor	Thermistor	Thermostat
Air Deflection		4-WAY	4-WAY	4-WAY	4-WAY	4-WAY	4-WAY	4-WAY	4-WAY
Fan Speeds:	Cooling / Heating	3	2 / 2	3	3	2 / 2	3	3	2 / 2
	Fan Only	3	1	3	3	1	3	3	1
Compressor		ROTARY	ROTARY	ROTARY	ROTARY	ROTARY	ROTARY	ROTARY	ROTARY
Type Air Discharge		TOP	TOP	TOP	TOP	TOP	TOP	TOP	TOP
Stale Air Exhaust		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Trim Kit		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Accessory Kit		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Sleeve & Rear Grille									
Sleeve with Expanded Aluminum Rear Grille		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Dimensions and Weight									
Chassis	Height (inches)	14 13/32	14 13/32	14 13/32	14 13/32	14 13/32	14 13/32	14 13/32	14 13/32
	Width (inches)	24	24 21/32	24	24	24 21/32	24	24	24 21/32
	Depth with front grille (inches)	20 3/32	19 21/32	20 3/32	20 3/32	19 21/32	20 3/32	20 3/32	19 21/32
Sleeve	Height (inches)	15 17/32	15 17/32	15 17/32	15 17/32	15 17/32	15 17/32	15 17/32	15 17/32
	Width (inches)	25 7/8	25 7/8	25 7/8	25 7/8	25 7/8	25 7/8	25 7/8	25 7/8
	Depth (inches)	16 23/32	16 23/32	16 23/32	16 23/32	16 23/32	16 23/32	16 23/32	16 23/32
	Depth with front grille (inches)	20 1/2	20 1/2	20 1/2	20 1/2	20 1/2	20 1/2	20 1/2	20 1/2
Net Weight w/o Sleeve (lbs.)		73	73	78	78	78	80	80	80
Shipping Weight w/o Sleeve (lbs.)		79	79	84	84	84	87	87	87

Sleeve Dimensions of Major Brands		Friedrich USC Sleeve	GE	Amana	Whirlpool Fedders	Frigidaire
Height (inches)		15 17/32	15 5/8	15 5/8	15 3/4	15 7/16
Width (inches)		25 7/8	26	26	26 3/4	25 7/8
Depth (inches)		16 23/32	16 7/8	16 7/8	15	18

Model	Circuit Rating Breaker or TD Fuse	Plug Face (NEMA#)	Appearance (Facing Blades)
US08B10A, UE08A13B US10B10A, US12B10A	125-15A	5-15P	
US10B30A, US12B30A	250V-15A	6-15P	
UE10A33B, UE12A33B	250V-20A	6-20P	



As an ENERGY STAR® partner, Friedrich Air Conditioning Co. has determined that the selected ENERGY STAR® models (★) meet the ENERGY STAR® guidelines for energy efficiency.

